



ALUMINUM BRONZE

EQUIVALENT SPECIFICATIONS

European CuAl10Fe1

C62300 aluminum bronze applications include valve and pump components for industrial process streams, as well as for marine equipment, high strength fasteners and pole line hardware.

TYPICAL USES :

FASTENERS: Nuts, Bolts **INDUSTRIAL:** Gears, Bearing Races, Valve Stems, Worm Gears, Valve Guides, Valve Seats, Bearings, Bushings, Cams, Pump Rods **MARINE:** Marine Hardware

CHEMICAL COMPOSITION

	Al	Cu	Fe	Mn	Ni	Si	Sn
Min/Max	8.5 - 10.0	Rem	2.0 - 4.0	0.5	1	0.25	0.6
Nominals	10.0000	87.0000	3.0000	-	-	-	-

PHYSICAL PROPERTIES

Product Property	US Customary
Coefficient of Thermal Expansion	9.0 $\times 10^{-6}$ per of (68-572 F)
Density	0.277 lb/in ³ @ 68 F
Electrical Conductivity	12 %IACS @ 68 F
Electrical Resistivity	86.4 ohms-cmil/ft @ 68 F
Melting Point Liquid US	1915 F
Melting Point Solid US	1905 F
Modulus of Elasticity in Tension	17000 ksi
Modulus of Rigidity	6400 ksi
Specific Gravity	7.67
Specific Heat Capacity	0.09 Btu/lb/ Δ° F @ 68 F
Thermal Conductivity	31.0 Btu Δ° ft/(hr Δ° ft ² Δ° F) @ 68 F

SIZES AVAILABLE :

ROUND RODS	8mm To 100 mm
HEX	10mm To 60mm
SQUARE	10mm To 60mm
FLAT	10mm Min Thickness and max Width 120mm
BILLETS	Up to 200 mm
INGOTS	As per Specification

Regd. Office & Plant
 Plot No. 6 & 7, Village: Lakhabaval, Post: Khodiyar Colony, Jamnagar - 361006.
 Tel.: +91-288-2889251 / 52, Fax: +91-288-2889223, Cell: +91-9924443396
 Email: info@metalalloyscorp.com • web: www.metalalloyscorp.com



ENGINEERS INDIA LIMITED
(A Govt. of India Undertaking)